

DECLARATION OF PERFORMANCE

according Annex III of the Regulation (EU) No 305/2011 amended by Commissions delegated Regulation (EU) No 574/2014



KÖSTER TPO Pro 1.2

RT 812 Pro

3.

4.

5.

6.

System of AVCP:

Notified body:

Harmonized standard:

1. Unique identification code of the KÖSTER TPO Pro 1.2 product-type: Nr. RT 812 Pro 251006

2. Intended use: Polyolefin based waterproofing membrane

with centrally embedded glass fleece according to the EN 13956:2012 for waterproofing flat and sloped roofs. Application by loose laying with ballast or

mechanical fastening

KÖSTER BAUCHEMIE AG

Manufacturer:
Dieselstraße 1 - 10
26607 Aurich

System 2+

EN 13956:2012

Materialprüfanstalt (MPA) für das Bauwesen,

Beethovenstraße 52 38106 Braunschweig

Identification number 0761-CPD









7. Declared performance:

Essential characteristics	Performance	System of assessment and verification of constancy of performance	Harmonised technical specification
Reaction to fire	Class E		
Water tightness Method B	≥ 400 kPa/72 h	System 2+ EN 13956:2012	
Tensile characteristics Tensile strength Elongation at break	≥ 5 N/mm ² ≥ 350 %		
Resistance to static load Method B	≥ 20 kg		
Resistance to shock loads Method A Method B	≥ 400 mm ≥ 1000 mm		
Tear continualtion resistance	≥ 175 N		
Peel resistance of the overlap	≥ 300 N/50 mm		
Resistance of the joint seams to shearing	Failure beyond the overlap		
UV resistance EN 1297	≥ 5000 h passed (grade 0)		
Exposure to bitumen	passed		
Exposure to liquid chemicals includong water	passed		
Folding at low temperatures	≤ - 30 °C		









The performance of the product according to point 1 and 2 corresponds to the declared performance of point 7. The manufacturer according to point 3 is solely responsible for the production of this service.

Signed for and on behalf of the manufacturer by:

Dr. Thorsten Lauterbach (Research and development)

Aurich, 06.10.2025

(place and date of issue)

i.V. gentandas (signature)



