



## KÖSTER TPO SK Primer

Technical Data Sheet RT 103 012

Issued: 2019-10-07

### Solvent based synthetic resin primer for KÖSTER TPO SK (FR) Membranes

#### Features

Solvent based synthetic resin primer.

KÖSTER Universal Cleaner

Prod. code X 910 010

#### Technical Data

Active ingredient content	15 %
Minimum application temperature	0 °C
Density	0.90 g / cm <sup>3</sup>
Drying time (+ 15 °C)	approx. 20 min.

#### Fields of Application

Primer for the application of KÖSTER TPO SK (FR) Membranes suitable for a variety of substrates including:

- Bitumen
- Sanded and crushed slate coated bitumen roofing membranes
- Concrete
- Wood composite materials such as OSB and maritime plywood boards
- Problem substrates (after consultation with KÖSTER BAUCHEMIE AG)

#### Substrate

The substrate must be sound and solid as well as free of bond inhibiting agents such as dust, grease, and oil.

#### Application

KÖSTER TPO SK Primer is applied over the entire surface using a roller or brush. The primer must be completely dry before installing KÖSTER TPO SK (FR) Membranes.

#### Consumption

approx. 200 g/m<sup>2</sup>

#### Cleaning

Clean immediately after use with KÖSTER Universal Cleaner.

#### Packaging

RT 103 012 12 kg bucket

#### Storage

In originally sealed packages the material can be stored for a minimum of 12 months. Observe the regulations for the storage of flammable liquids.

#### Safety

Wear solvent-protective gloves and goggles when processing the material. Use only in well ventilated areas. Observe all governmental, state, and local safety regulations when processing the material.

#### Related products

KÖSTER TPO 1.5 SK (FR) Prod. code RT 815 SK (FR)  
)

The information contained in this technical data sheet is based on the results of our research and on our practical experience in the field. All given test data are average values which have been obtained under defined conditions. The proper and thereby effective and successful application of our products is not subject to our control. The installer is responsible for the correct application under consideration of the specific conditions of the construction site and for the final results of the construction process. This may require adjustments to the recommendations given here for standard cases. Specifications made by our employees or representatives which exceed the specifications contained in this technical guideline require written confirmation. The valid standards for testing and installation, technical guidelines, and acknowledged rules of technology have to be adhered to at all times. The warranty can and is therefore only applied to the quality of our products within the scope of our terms and conditions, not however, for their effective and successful application. This guideline has been technically revised; all previous versions are invalid.

KÖSTER BAUCHEMIE AG • Dieselstraße 1-10 • D-26607 Aurich • Tel. 04941/9709-0 • Fax -40 • info@koester.eu • www.koester.eu